TOSHIBA

e-STUDIO2329A

- Black & White MFP
- 23 PPM
- Small Work Group
- Copy, Print, Scan, Fax
- Mobile Enabled



This professional monochrome MFD delivers flexibility and efficiency for your office. Compact in design, the e-STUDIO2329A is a cost effective Ledger size (A3) BW print device with a small footprint.

Whatever you need, Toshiba e-STUDIO2329A is packed with multifunctional potential including colour scanning and flexible mobile capabilities.

Add the optional fax and the system comfortably meet all demands of the modern office environment.

e-STUDIO2329A

Specifications

Copying/Printing Process	Indirect Electrostatic Photographic Method
Type	Desktop
Original Scanning Method	Contact Image Sensor (CIS)
Resolution	2400 x 600 dpi (with Smoothing)
Gradation	256 Steps
Original Platen Type	Fixed Hard Platen, Optional 50-Sheet RADF (14-28 lb)
Available Original Size	ST-R to LD
Maximum Paper Size	Drawer: LD Stack Feed Bypass: ST-R, LT, LG, LD, Envelope
Paper Supply	Standard: Drawer (250 Sheets x 1) Stack Feed Bypass (100 Sheets) Max.: 1,700 (Optional 250 Sheets x 1, 550 Sheets x 2)
Available Paper Weight	Drawer: 17-20 lb (Including Optional Paper Sources) Stack Feed Bypass: 14-120 lb Index Auto Duplexing Unit: 17-20 lb
Paper Exit	Face Down/Inner Tray
Warm-up Time	Approx. 15 Seconds (Scanner Function Available During Warm-Up)
Counter	Electronic Counter (Indication by LCD Display)
Memory	512 MB (1GB when PostScript is installed)
Department Codes	100
Power Supply	115 Volts, 12 Amps
Power Consumption	Maximum: 1.5kW
Dimensions	Standard: Approx. 22.6" x 21.2" x 16" (W x D x H) With PFU: Approx. 23" x 22.2 x 20" (W x D x H)
Weight	Approx. 59.4 lb
Special Features	Energy Saver, Auto Sleep Mode, Department Code
Max Duty Cycle	64K Copies
Certifications	Energy Star V3.0, EPEAT (GOLD), California Prob 65, Eco Leaf (English Version)
Worldwide Safety Stds.	cULus, UL, C-UL, CDRH
Black Toner Yield	17.5 K impressions based on 5% coverage

Copy Specifications

Copying Speed	23 PPM
Original Scan Speed	25 SPM (by Using RADF)
Scan Resolution	600 x 600 dpi (for Copying)
First Copy Time	Less Than 6.5 Seconds
Original/Copy Size	ST-R to LD
Original Mode	Photo, Text/Photo, Text, Background Erase
Image Density Control	Automatic/Manual (9 Steps)
Reproduction Ratio	Zoom: 25% to 400% in 1% Increments
Multiple Copying	Up to 999 Copies (Ten Key Input)
Special Features	Department Codes (100), Interrupt, APS/AMS, Auto Job Start, Automatic Sort Mode, ID Card Copy, One Touch Key (2)

Print Specifications (Standard)

Printing Speed	23 PPM
Printing Resolution	2400 x 600 dpi (with Smoothing)
Interface	Standard: 10/100 Base-T, USB 2.0 Optional: IEEE802.11 b,g,n
PDL	PCL 6 Emulation Optional: PostScript 3 (upgrades memory to 1GB)
USB Direct Printing	JPEG, TIFF, PDF (Only PDF Created by MFP Can Be Printed Unless PS3 Option Installed)
Support OS	Windows 7, 8, 8.1, 10, 2008R2, 2012, 2012 R2, 2016, (WHQL), CUPS PCL Unix, Linux 5.10.x, 6.5.x

Scan Specifications (Standard)

Connection Type	Standard: 10/100 Base-T Optional: IEEE802.11 b,g,n
Scanning Resolution	100/150/200/300/400/600 dpi
Scanning Speed	25 SPM (BW) at 600 dpi, 24 SPM (Colour) @ 200 dpi, 18 SPM @ 300 dpi
Scan Agent	Scan to File, SMB, FTP, Scan to Email, Scan to USB, TWAIN

Paper Handling

Reversing Automatic Document Feeder (RADF)

Stack Capacity	50 Sheets
Original Setting	Original Setting Face Up
Original Paper Size	ST-R to LD
Original Paper Weight	14-28 lb

FAX Specifications (optional)

Compatibility	Super G3, G3
Image Format on PSTN	JBIG, MMR, MR, MH
Document Size	ST-R-LD
Modem Speed	33.6 kbps to 2.4 kbps (Automatic Fallback)
Transmission Speed	Approx. 3 Seconds
Communication Protocols	ITU-T T.30
Memory Transmission	Max 256 Jobs, 220 Destinations/Job, 384 Pages/File

Options

Platen Cover	KA-2507PC
Reversing Automatic Document Feeder (RADF)	MR-3032
2nd Paper Cassette	MY-1043-B
Paper Feed Pedestal, including 3rd Paper Cassette	KD-1039-B
4th Paper Cassette	MY-1044-B
Cabinet	ST-2007
Fax Kit	GD-1380
PostScript 3	GA-1350L
Wireless LAN Module	GN-1160
Harness for Coin Controller	GQ-1131

Designs and specifications subject to change without notice. Specifications may vary by conditions of use and/or environmental usage. For best results and reliable performance, always use supplies manufactured or designated by Toshiba. Not all options and accessories may be available at the time of product launch. Please contact a local Authorized Toshiba Dealership or Toshiba Tec Canada Business Solutions Inc. Branch for availability. Toner yields are estimates based on 5% coverage, letter-size page. Driver and connectivity feature support varies by client/network operating system. Product names may be trademarks of their respective companies. AirPrint® and the AirPrint® logo are trademarks of Apple Inc. This is a Class 1 laser product complying with IEC60825-1. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

© 2019 Toshiba Tec Canada Business Solutions Inc.
Inv. Code CE-ES2329A-B

Corporate Office 75 Tiverton Court
Markham, Ontario
L3R 4M8

Phone 905-470-3500
Fax 905-470-3450

Web Site www.toshibatec.ca